

Survey of the subdivisions of T. 25 N., R. 46 E.

Chains.  
 76.50 Top of low spur, projects NE. Desc. N. slope 10 ft.  
 80.02 The cor. of secs. 1, 2, 11 and 12.  
 Land, mountainous. Soil, light, rocky and gravelly clay.  
 Undergrowth, sage; scant growth of grass. Timber,  
 pinon pine and juniper.

N. 0° 01' W., bet. secs. 1 and 2.

Desc. N. slope 100 ft. over mountainous land, through dense pinon and juniper.

9.10 Dry wash, drains E. Asc. gradual S. slope 30 ft.

14.80 Slope changes to NE. Desc. 170 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

A pinon 5 ins. in diam., bears N. 2-3/4° E., 97 lks. distant, marked  $\frac{1}{4}$  S1 BT

A pinon 10 ins. in diam., bears S. 45° W., 16 lks. distant, marked  $\frac{1}{4}$  S2 BT

Desc. NE. slope 160 ft.

69.90 Dry wash, drains NW. Asc. S. slope 100 ft.

80.40 Point of spur, projects NW. Desc. N. slope 70 ft.

85.10 Short wash, drains W. Asc. SW. slope 40 ft.

89.92 Intersect the Fifth Standard Parallel North, at a point, East, 5.17 chs. distant, from the Standard  $\frac{1}{4}$  sec. cor. of sec. 35, which is an iron post, 1 in. in diam., firmly set and properly marked and witnessed as described in the field notes of T. 26 N., R. 46 E.

At the point of intersection, set an iron post, 3 ft. long, 2 ins. in diam., 30 ins. in the ground, on steep SW. slope, for the closing cor. of secs. 1 and 2, with brass cap mkd.

