

Survey of the subdivisions of T. 25 N., R. 46 E.

Chains.

20.00 Top of spur, projects NW. Desc. abrupt N. slope 270 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S4} | \text{S3} \\ 1926 \end{array}$$

from which

A juniper, 10 ins. in diam., bears S. $30\frac{1}{4}^{\circ}$ E., 25 lks. distant, marked $\frac{1}{4}$ S3 BTA juniper, 8 ins. in diam., bears N. 19° W., 19 lks. distant, marked $\frac{1}{4}$ S4 BT

Desc. N. slope 170 ft. to Dry wash.

48.50 Leave dense pinon pine and juniper, bears E. and W.; enter scattering juniper.

64.30 Dry wash, drains NW. Desc. 70 ft.

89.81 Intersect the Fifth Standard Parallel North, at a point, East, 5.60 chs. distant, from the standard $\frac{1}{4}$ sec. cor. of sec. 33, which is an iron post, 1 in. in diam., firmly set, properly marked and witnessed, as described in the field notes of T. 26 N., R. 46 E.

At the point of intersection, set an iron post, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 3 and 4, with brass cap mkd.

$$\begin{array}{c} \text{T26N R46E} \\ \text{S33} \\ \hline \text{S4} | \text{S3} \\ \text{T25N R46E} \\ \text{C} | \text{C} \\ 1926 \end{array}$$

from which

A juniper, 6 ins. in diam., bears S. 81° W., 194 lks. distant, marked CC T25N R46E S4 BT

No other bearing tree available. Raise a mound of stone, 3 ft. base, 2 ft. high, S. of the cor.

Land: S. half, mountainous; N. half, slightly rolling.

Undergrowth, sage; scant growth of grass. Timber, pinon pine and juniper.