

## Survey of the subdivisions of T. 25 N., R. 46 E.

## Chains.

- 46.60 Top of spur, projects NE. Desc. N. slope 20 ft.  
 49.20 Dry wash, drains NE. Asc. S. slope 80 ft. to top of spur.  
 57.00 Spring bears S.  $66^{\circ} 15'$  W.  
 63.10 Top of spur, projects NE. Desc. NW. slope 60 ft.  
 66.70 Dry wash, drains NE. Asc. S. slope 90 ft.  
 82.60 Top of spur, projects E. Desc. N. slope 100 ft.  
 88.70 Dry wash, drains N.  $60^{\circ}$  E. Asc. S. slope 40 ft.  
 89.58 Intersect the Fifth Standard Parallel North, at a point, East, 5.94 chs. distant, from the standard  $\frac{1}{4}$  sec. cor. of secs. 31, which is an iron post, 1 in. in diam., firmly set, properly marked and witnessed, as described in the field notes of T. 26 N., R46 E.  
 At the point of intersection, set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 6 and 7, with brass cap mkd.

T26N R46E  
 S31  
 S6 S5  
 T25N R46E  
 C C  
 1926

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of the cor.

Land, rolling. Soil, gravelly and rocky clay. Undergrowth, sage; scant growth of grass. Timber, juniper and pinon pine.

## Latitudes, Departures and Closing Errors.

Line Designated	True Bearing	Dist- ance	Latitudes N.      S.	Departures E.      W.
E. Bdy.	North	490.31	490.31	
N. Bdy.	West	480.87		480.87
W. Bdy.	South	489.61	489.61	
S. Bdy.	East	482.07		482.07
Convergency				.61
			490.31 489.61 482.07 481.48	
			489.61	481.48
Error in latitude			.70	
Error in departure				;59