

Survey of the Fifth Standard Parallel North through R. 46 E.

Chains

Land, rolling mountainous. Soil, rocky, gravelly, sandy clay. Undergrowth, sage, scattering shadscale and grass. Timber, scattering juniper and pinon pine.

West, on a true line, on the S. Bdy. of sec. 31.

Asc. SE. slope 20 ft. over rolling land through scattering juniper and pinon pine.

3.50 Top of spur, projects N. 30° E. Desc. along N. slope 50 ft. to

39.10 Dry wash, course NE. Asc. SE. slope 300 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground to solid rock and 12 ins. in a mound of stone, for the Std. $\frac{1}{4}$ sec. cor., with brass cap mkd.

SC
 $\frac{1}{4}$ S31
1925

Deposit a granite stone 8x10x12ins., with cross marked (X) at base of post. No bearing trees or other accessories available.

60.40 Desc. NW. slope 30 ft. to

Top of low ridge, bears NE. and SW.

80.00 Set an iron post, 3 ft. long, 3 ins. in diam., 17 ins.

in the ground to solid rock and 18 ins. in a mound of stone for Std. cor. of T.26 N., Rs.45 and 46 E., with brass cap mkd.

SC
T26N
R45E R46E
S36 S31
1925

Deposit a granite stone 10x8x6 ins., with cross marked (X) at base of post. No bearing trees or other accessories available.

Land, rolling. Soil, rocky, gravelly, sandy clay.

Undergrowth, sage, scattering shadscale and grass.

Timber, scattering juniper and pinon pine.