

Survey of the West Boundary of T. 26 N., R. 46 E.

Chains
74.00 Shallow wash, course NE. Asc. along gradual E. slope.
80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for cor. to secs. 1, 6, 7 and 12, with brass cap mkd.

| | |
|------|------|
| T26N | |
| R45E | R46E |
| S1 | S6 |
| S12 | S7 |
| 1925 | |

raise a mound of stone, 3 ft. base, 1½ ft. high W. of corner. No bearing trees or other accessories available.

Land, slightly rolling. Soil, rocky, gravelly clay sand. Undergrowth, sage, shadscale and scant growth of grass. No timber.

North, on a true line, bet. secs. 1 and 6.

Asc. along E. slope 50 ft. to

30.00 E. side of low butte. Desc. N. slope 60 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

| | |
|------|----|
| ¼ | |
| S1 | S6 |
| 1925 | |

raise a mound, of stone, 3 ft. base, 1½ ft. high W. of corner. Desc. gradual N. slope.

49.80 Wash, course NE. Continue gradual descent of general NW. slope.

70.00 Road, bears NE. and SW.

76.20 Dry wash, course NE.

78.78 Intersect the S. Bdy. of T. 27 N., R. 46 E., at a point, N. 89° 54' E., 44.37 chs. dist. from the cor. of T. 27 N., Rs. 45 and 46 E. which is an iron post, 3 ins. in diam., firmly set, and properly marked and witnessed, as described in the field notes of T. 27 N., R. 46 E.

At the point of intersection set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, for the