

Survey of the Subdivisions of T. 26 N., R. 46 E.

Chains	T26N R46E S26 S25 S35 S36 1925
	raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high W. of corner.
	Land, rolling and broken mountainous. Soil, light, sandy, gravelly and rocky clay. Undergrowth, sage, shadscale, fair growth of grass. Timber, pinon pine and juniper.

	East, on a random line, bet. secs. 25 and 36.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Fall 9 lks. N. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 26 N., R. 47 E.
	Thence
	✓ N. $89^{\circ} 56'$ W. on a true line bet. secs. 25 and 36.
	Desc. broken SW. slope through dense pinon pine timber.
6.80	Dry wash, course SW.
10.00	Leave dense pinon pine, bears N. and S.; enter scattering pinon pine and juniper. Asc. gradual SE. slope.
20.20	Top of spur, projects S. Desc. SW. slope 150 ft. to
35.00	Dry wash, course N. 10° W. Asc. NE. slope 25 ft. to
35.80	Road, bears SE. and NW.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 25 S 36 1925
	from which
	✓ A pinon pine, 12 ins. in diam., bears N. 33° E., 150 lks. dist., marked $\frac{1}{4}$ S25 BT
	✓ A pinon pine, 7 ins. in diam., bears S. $42\frac{3}{4}^{\circ}$ W., 11 lks. dist., marked $\frac{1}{4}$ S36 BT
44.70	Dry wash, course N. Asc. E. slope 80 ft. to spur.
45.50	Road, bears N. 10° E. and S. 10° W.
53.00	Top of spur, projects N. 10° E. Desc. W. slope 60 ft. to