

## Survey of the Subdivisions of T. 26 N., R. 46 E.

## Chains

sandy clay. Undergrowth, sage, shadscale and fair growth of grass. Timber, scattering juniper.

- 
- S. 89° 56' E., on a random line bet. secs. 24 and 25.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 80.04 Fall 26 lks. N. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 26 N., R. 47 E.
- Thence
- N. 89° 45' W., on a true line bet. secs. 24 and 25.
- Desc. SW. slope 260 ft. to dry wash over rolling land through scattering pinon pine and juniper.
- 18.80 Road, bears N. 30° W. and S. 30° E.
- 26.50 Wire fence, bears SE. and NW.
- 31.65 Road, bears S. 10° W. and N. 10° E.
- 34.15 Wire fence, bears N. and S.
- 35.00 Dry wash, course NW. Asc. NE. slope 20 ft. to
- 40.02 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- $$\frac{1}{4} \begin{array}{l} S 24 \\ S 25 \\ 1925 \end{array} \checkmark$$
- raise a mound of stone, 3 ft. base,  $1\frac{1}{2}$  ft. high N. of corner. No bearing trees available.
- 41.00 Low spur, projects NW. Desc. gradual SW. slope.
- 49.50 Dry wash, course N. 10° W. Asc. E. slope 60 ft. to spur.
- 53.50 Road, bears S. 10° E. and N. 10° W.
- 60.20 Spur, projects NW. Desc. W. slope 75 ft. to
- 74.15 Dry wash, course NW. Asc. NE. slope 45 ft. to
- 80.04 The corner of secs. 23, 24, 25 and 26.
- Land, rolling. Soil, light, gravelly, rocky, sandy clay. Undergrowth, sage, shadscale and fair growth of grass. Timber, pinon pine and juniper.
-