

Dependent Resurvey of the W. Bdy. of T. 27 N., R. 46 E.

Chains.

- From the $\frac{1}{4}$ sec. cor., N. $0^{\circ} 27'$ E., on a true line.
 Asc. SE. slope 50 ft.
- 43.00 Top of spur, projects SE. Desc. gradual NE. slope.
- 48.60 Dry wash, course SE. Asc. SE. slope 110 ft.
- 56.50 Top of spur, projects SE. Desc. NE. slope 50 ft.
- 59.10 Dry wash, course S. 60° E. Asc. SE. slope 100 ft.
- 72.60 Top of spur, projects S. 70° E. Desc. NE. slope 50 ft.
- 76.20 Dry wash, course S. 60° E. Asc. SE. slope 50 ft.
- 78.78 A northing of 80.00 chs. from the cor. of secs. 7 and 18. Set an iron post, 3 ft. long, 2 ins. in diam., 14 ins. in the ground, to solid rock, and 22 ins. in a mound of stone, for the cor. of secs. 6 and 7, with brass cap mkd.

| | |
|------|------|
| T27N | T27N |
| R45E | S6 |
| S12 | S7 |
| | R46E |
| | 1924 |

Deposit a quartzite stone, 10 x 8 x 5 ins., with cross marked (x), at base of post.

- 79.40 Top of spur, projects E. Desc. NE. slope 20 ft.
- 80.82 Intersect the old cor. of secs. 1, 6, 7 and 12, hereinbefore described. Alongside, set an iron post, 3 ft. long, 2 ins. in diam., 14 ins. in the ground, to solid rock, and 22 ins. in a mound of stone, for the cor. of sec. 1 and 12, with brass cap mkd.

| | |
|------|------|
| T27N | T27N |
| S1 | R46E |
| S12 | S6 |
| R45E | |
| | 1924 |

Deposit a quartzite stone, 10 x 8 x 5 ins., with cross marked (x), at base of post.

Land, rolling mountainous. Soil, light, sandy, gravelly and rocky clay. Undergrowth, sage, shadscale and scattering growth of grass.

N. $3^{\circ} 08'$ E., on a true line, on the E. Bdy. of sec. 1.
 Desc. NE. slope 20 ft. over rolling mountainous land.