

Survey of the E. Bdy. of T. 27 N., R. 46 E.

Chains.	
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.
42.00	Dry wash, course S. 70° E.
65.50	Dry wash, course S. 70° E.
83.20	Dry wash, course S. 80° E. Road, bears NW. and SE.
85.00	Top of low spur, projects S. 70° E.
94.70	Dry wash, course SE.
96.00	Intersect the S. Bdy. of T. 28 N., R. 47 E., at a point, S. $89^{\circ} 55'$ E., 42.56 chs. dist. from the SW. cor. of T. 28 N., R. 47 E., hereinbefore described. At the point of intersection, set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, for the closing cor. of T. 27 N., Rs. 46 and 47 E., with brass cap mkd.

T28N R47E

S31

S1 | S6

R46E | R47E

T27N

C C

1924

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of the cor.

Land, slightly rolling. Soil, light, sandy, gravelly and rocky clay. Undergrowth, shadscale, sage, and scant growth of grass.

Dependent Resurvey of a portion of the S. Bdy. of sec. 31,
T. 28 N., R. 47 E.

From the closing cor. of T. 27 N., Rs. 46 and 47 E.,
hereinbefore described,

N. $89^{\circ} 55'$ W., on a true line, bet. secs. 1 and 31.

Asc. SE. slope 200 ft. over rolling land, to top of spur.

8.90 Road, bears NW. and SE.

26.50 Top of low spur, projects NE. Asc. 30 ft. along N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.
in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 1, with
brass cap mkd.