

Survey of the S. Bdy. of T. 27 N., R. 46 E.

Chains.

stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \text{ S36} \\ \hline \text{S1} \\ 1924 \end{array}$$

Deposit a granite stone, 8 x 8 x 5 ins., with cross marked (x), at base of post.

Desc. NE. slope 60 ft.

44.40 Dry wash, course N.

51.00 Dry wash, course NW. Asc. W. slope 240 ft.

66.90 Top of ridge, bears N. and S. Desc. SE. slope 270 ft.

80.00 Intersect the cor. of Ts. 26 and 27 N., Rs. 46 and 47 E., hereinbefore described.

Land, rolling. Soil, slight, sandy, gravelly and rocky clay. Undergrowth, sage, shadscale and scant growth of grass.

Survey of the subdivisions of T. 27 N., R. 46 E.

From the cor. of secs. 1, 2, 35 and 36, on the S. Bdy. of the township,

N. $0^{\circ} 01'$ W., on a true line, bet. secs. 35 and 36.

Desc. N. slope 20 ft. over slightly rolling land.

5.00 Dry wash, course NW. Desc. gradual N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.

in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S35} \mid \text{S36} \\ \hline 1924 \end{array}$$

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.

42.00 Dry wash, course N. 20° W.

60.00 Dry wash, course N. 20° E.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins.

in the ground, for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

$$\begin{array}{c} \text{T27N} \mid \text{R46E} \\ \hline \text{S26} \mid \text{S25} \\ \hline \text{S35} \mid \text{S36} \\ 1924 \end{array}$$