

## Dependent Resurvey of the Nevada-Oregon State Line along the

N. Bdy. of T. 47 N., R. 33 E.

Chains.	Desc. W. slope 90 ft. over rough mountainous land.
19.80	Dry wash, course S. 60° W. Desc. along general S. slope 420 ft.
53.45	A westing of 40.00 chs. from the cor. of secs. 5 and 6. Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground, to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor. for sec. 6, with brass cap mkd.
	<u>ORE</u> $\frac{1}{4}$ S6 1924
	Deposit a granite stone, 8 x 6 x 4 ins., with cross marked (x), at base of post.
	Desc. along S. slope 390 ft.
75.50	Dry wash, course NW.
79.45	Intersect the 219th mile post, hereinbefore described.
	Land, rough mountainous. Soil, sandy, gravelly and rocky clay. Undergrowth, scattering sage and scant growth of grass.
	-----
	Retracement of the S. Bdy. of T. 47 N., R. 33 E.
	-----
	From the cor. of Ts. 46 and 47 N., R. 33 E., which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed as described in the field notes of T. 46 N., R. 34 E., West, on retracement, along the S. Bdy. of T. 47 N., R. 33 E., setting temporary points at 40.00 and 80.00 chs. and making diligent search for old corners. No trace of the old corners were found until a point
162.76	Fall 147 lks. S. of the old cor. of secs. 2, 3, 34 and 35, which is a volcanic stone, 24 x 12 x 10 ins., firmly set in a mound of stone, marked with 2 grooves on E. face; 4 grooves on W. face and 6 grooves on S. face.
	The course of this line is N. 89° 29' W. and the dist. is 162.76 chs.
	-----

Dist. is 162.76 chs.