

Dependent Resurvey of the S. Bdy. of T. 47 N., R. 33 E.

Chains.

40.06 Intersect the old $\frac{1}{4}$ sec. cor., hereinbefore described. Alongside, set an iron post, 3 ft. long, 1 in. in diam., 14 ins. in the ground, to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor. for sec. 6, with brass cap mkd.

$\frac{1}{4}$ S6
1924

Deposit a volcanic stone, 6 x 4 x 4 ins., with cross marked (x), at base of post.

From the $\frac{1}{4}$ sec. cor., N. $88^{\circ} 54'$ W., on a true line. Asc. NE. slope 30 ft.

55.00 Top of spur, projects SE. Desc. SW. slope 30 ft.

69.70 Road, bears NW. and SE.

70.00 House Creek, course SE.; intermittent stream of water.

72.70 Road, bears NE. and SW. Asc. E. slope 30 ft.

77.92 Intersect the cor. of Ts. 46 and 47 N., R. 33 E., hereinbefore described.

Land, rolling. Soil, rocky, gravelly and sandy clay. Undergrowth, medium to dense growth of sage and scant growth of grass. *stop*

Survey of the subdivisions of T. 47 N., R. 33 E.

From the cor. of secs. 25 and 36, on the E. Bdy. of the township, which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed as described in the field notes of T. 47 N., R. 34 E., West, on a sectional correction line, bet. secs. 25 and 36.

Asc. 20 ft. along S. slope over broken mountainous land.

4.80 Point of spur, projects SW. Desc. W. slope 200 ft.

12.60 China Creek, course SW. No water. Spring bears S. 45° W., 8.00 chs. dist. Asc. SE. slope 10 ft.

13.30 Dim road, bears NE. and SW.

15.80 Point of spur, projects S. Desc. SW. slope 90 ft.

19.00 Dry wash, course S. 30° E. Asc. along SE. slope 350 ft.