

Survey of the subdivisions of T. 47 N., R. 33 E.

Chains.

77.60 Top of spur, projects SW. Asc. gradually along SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 23, 24, 25 and 26, with brass cap mkd.

T47N | R33E
S23 | S24
S26 | S25
1924

Deposit a granite stone, 5 x 5 x 4 ins., with cross marked (x), at base of post.

Land, broken and rough mountainous. with numerous outcroppings of granite formation. Soil, rocky, decomposed granite. Undergrowth, medium growth of sage and scant growth of grass.

East, on a random line, bet. secs. 24 and 25.

40.00 Set temp. 1/4 sec. cor.

79.72 Fall 5 lks. N. of the cor. of secs. 24 and 25 on the E. Bdy. of the township, which is an iron post, 2 ins.

in diam., firmly set and properly marked and witnessed as described in the field notes of T. 47 N., R. 34 E.

Thence

N. 89° 58' W., on a true line, bet. secs. 24 and 25.

3.00 Dry wash, course S. Asc. SE. slope 230 ft. over broken mountainous land.

9.40 Top of spur, projects SE. from NE. Desc. SW. slope 300 ft.

19.50 Dry wash, course SE. Asc. broken E. slope 460 ft.

39.86 Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground, to solid rock, in a mound of stone, 5 ft. base, 30 ins. high, for the 1/4 sec. cor., with brass cap mkd.

S 24
1/4
S 25
1924

From which

A cross marked (x) and B0 on base of granite ledge, 35 ft. high, 30 ft. wide, bears W., 14 lks. dist.