

Survey of the subdivisions of T. 47 N., R. 33 E.

Chains

cap mkd.

S30

$\frac{1}{4}$

S31

1924

Deposit a volcanic stone, 6 x 5 x 4 ins., with cross marked (x), at base of post.

42.00 Dry wash, course NW. Desc. 20 ft. along W. slope.

44.20 Road, bears N. and S.

46.70 Kings River, course S.; running water, 6 lks. wide, 6 ins. deep. Dense willows along river bottom.

Asc. NE. slope 340 ft.

74.70 Top of spur, projects SE. Asc. SE. slope 140 ft.

88.40 Top of ridge, bears NE. and SW.

88.49 Intersect the W. Bdy. of the twp., at a point, North 16.66 chs. dist. from the cor. of secs. 25 and 36, T. 47 N., R. 32 E., hereinafter described. At the point of intersection, set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 30 and 31, with brass cap mkd.

T47N	S30	C
R32E	S31	C
S25	R33E	
1924		

Raise a mound of stone, 2 ft. base, 1½ ft. high, E. of the cor.

Land, broken mountainous. Soil, sandy and gravelly clay. Undergrowth, medium growth of sage and scant growth of grass. Willows and aspen along Kings River.

From the cor. of secs. 29, 30, 31 and 32,

N. 0° 04' W., on a true line, bet. secs. 29 and 30.

Asc. SE. slope 170 ft. over broken mountainous land.

19.80 Top of ridge, bears NE. and SW. Desc. along W. slope 120 ft.

38.60 Dry wash, course SW. Asc. SE. slope 20 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground, to solid rock, in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.