

Survey of the subdivisions of T. 47 N., R. 33 E.

Chains. and rocky clay. Undergrowth, medium to dense growth of sage and scattering growth of grass.

West, on a true line, bet. secs. 18 and 19.

.50 Point of spur, projects SW. Desc. W. slope 320 ft. over rough mountainous land.

13.20 Wire fence bears N. and S. Desc. W. slope 40 ft.

15.30 Kings River, course S.; running water, 4 lks. wide, 4 ins. deep. Dense growth, aspen, willows and choke-cherry along river bottom. Asc. SE. slope 60 ft.

19.90 Wire fence bears N. and S.

20.20 Road, bears N. and S. Asc. SE. slope 30 ft.

31.80 Wire fence, bears NW. and SE.

33.30 Creek, course SE.; running water, 2 lks. wide, 2 ins. deep. Asc. NE. slope 100 ft.

38.90 Wire fence bears N. and S. Asc. NE. slope 30 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in the ground, to solid rock, and 26 ins. in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S18
 $\frac{1}{4}$
S19
1924

Deposit a volcanic stone, 6 x 5 x 5 ins., with cross marked (x), at base of post.

Asc. along N. slope 260 ft.

58.00 Slope changes to NW. desc. 50 ft.

72.80 Dry wash, course NE. Asc. E. slope 470 ft.

88.57 Intersect the W. Bdy. of the township, at a point, North, 16,42 chs. dist. from the cor. of secs. 13 and 24, T. 47 N., R. 32 E., hereinafter described. At the point of intersection, set an iron post, 3 ft. long, 2 ins. in diam., 20 ins. in the ground, to solid rock, and 16 ins. in a mound of stone, for the closing cor. of secs. 18 and 19, with brass cap mkd.

T47N 32	T47N
R32E 13	S18 C
S13 19	S19 C
	R33E

1924