

## Dependent Resurvey of the W. Bdy. of T. 46 N., R. 35 E.

Chains.

Alongside the old Std. cor. of Ts. 46 N., Rs. 34 and 35 E., hereinbefore described, set an iron post, 3 ft. long, 3 ins. in diam., 6 ins. in the ground, to solid rock, in a mound of stone, 6 ft. base, 30 ins. high, for the Std. cor. of T. 46 N., R. 35 E., with brass cap mkd.

S C
T46N
R35E
S31

1923

Deposit a volcanic stone, 10 x 8 x 6 ins., with cross marked(X), at base of post.

Thence

N. 0° 12' E., on a true line, on the W. Bdy. of sec. 31. Asc. gradual SW. slope over rolling mesa land.

40.28 Intersect the  $\frac{1}{4}$  sec. cor. for secs. 31 and 36, hereinbefore described. Alongside, set an iron post, 3 ft. long, 1 in. in diam., 14 ins. in the ground, to solid rock, in a mound of stone, for the  $\frac{1}{4}$  sec. cor. for sec. 31, with brass cap mkd.

$\frac{1}{4}$
S31

1923

Deposit a volcanic stone, 10 x 8 x 4 ins., with cross marked (x), at base of post.

44.10 From the  $\frac{1}{4}$  sec. cor., N. 0° 13' E., on a true line. Top of low ridge, bears NW. and SE. Desc. gradual NE. slope.

46.17 A northing of 40.00 chs. from the Std. closing cor. of Ts. 45 and 46 N., R. 34 E., hereinafter determined. Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. for sec. 36, with brass cap mkd.

$\frac{1}{4}$
S36

1923

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of the cor.

76.20 Top of low ridge, bears SW. and NE.  
Desc. gradual NW. slope.