	-	Dependent Resurvey of the E. Bay. of T. 46 N., R. 33 E.
	Chains.	T46N S1 T46N S12 R34E R33E S6 1923
		Deposit a granite stone, 6 x 5 x 4 ins., with cross
-	. 11	marked (x) at base of post.
		Land, broken and choppy. Soil, sandy and rocky clay
		loam with rocky subsoil. Undergrowth, medium growth.
-		of sage and scattering grass. Poor grazing.
-		
-		N. 0° 36' E., on a true line, on the E. Bdy. of sec. 1.
STATE OF THE PERSON ASSESSMENT		Over rolling land.
-	2.70	Dry wash, course SW. Asc. SW. slope 130 ft.
	20.00	Top of low spur, projects SW. Desc. NW. slope 20 ft.
	33.59	True point for the $\frac{1}{4}$ sec. cor. for sec. 6, hereinafter
		determined.
-		Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.
-		in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 6, with
	.47	brass cap mkd.
		\$6 1923
STATE STATE OF STREET, STATE S		Raise a mound of stone, 2 ft. base, 12 ft. high, E.
-		of the cor.
-	34.30	Dry wash, course SW. Asc. along W. slope 130 ft.
and the second second	40.40	The proportionate point.
-		Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.
-		in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 1, with
-		brass cap mkd.
-	.50	\frac{1}{4} \\ \S1 \\ 1923
-		Raise a mound of stone, 2 ft. base, la ft. high, W.of
-		the cor.
-		Asc. along W. slope 100 ft.
-	58.00	Dry wash, course SW. Asc. SW. slope 200 ft.
-	80.80	Intersect the cor. of Ts. 46 and 47 N., Rs. 33 and 34 E.,
-	r - 2' 5'	hereinbefore described. Alongside, set an iron post,
-	et 2	3 ft. long, 3 ins. in diam., 27 ins. in the ground,
1		