

## Survey of the subdivisions of T. 46 N., R. 34 E.

Chains.

in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S31} \mid \text{S32} \\ 1923 \end{array}$$

Deposit a granite stone, 10 x 8 x 3 ins., with cross  
marked (x) at base of post.

43.10 Horse Creek, course W., dry at this point.

55.00 Road, bears E. and W.

79.18 Intersect the S. Bdy. of Twp., at a point, S. 89° 15' E.,  
2.55 chs. dist. from the angle point, for the old Std.  
 $\frac{1}{4}$  sec. cor., hereinbefore described.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins.  
in the ground, for the closing cor. of secs. 31 and  
32, with brass cap mkd.

$$\begin{array}{c} C \mid C \\ \text{T46N} \mid \text{R34E} \\ \text{S31} \mid \text{S32} \\ S6 \\ \text{T45N} \mid \text{R34E} \\ 1923 \end{array}$$

Deposit a granite stone, 8 x 5 x 4 ins. with cross  
marked (x) at base of post.

Land, nearly level. Soil, sandy and rocky.

Undergrowth, medium growth of sage and scattering grass.

From the cor. of secs. 29, 30, 31 and 32,  
N. 0° 11' W., on a true line, bet. secs. 29 and 30.  
Asc. SW. slope over slightly rolling land.

9.00 Wire fence bears NE. and SW.

15.00 Shallow wash, course W. Asc. SW. slope 90 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.  
in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap  
mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S30} \mid \text{S29} \\ 1923 \end{array}$$

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
of the cor.

43.10 Dry wash, course W. Asc. SW. slope 160 ft.

54.70 Top of spur, projects W. Desc. NW. slope 60 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 18 ins.