

## Survey of the subdivisions of T. 46 N., R. 34 E.

Chains.

West, on a true line, bet. secs. 19 and 30.

Desc. W. slope over rolling land.

5.60 Road, bears NE. and SW.

5.90 Dry wash, 150 ft. below sec. cor., course SW.

Asc. SE. slope 100 ft.

21.10 Top of spur, projects SW. Desc. W. slope 270 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.  
in the ground, for the  $\frac{1}{4}$  sec. cor. for sec. 30, with  
brass cap mkd.

$\frac{1}{4}$ S30
1923

Deposit a granite stone, 6 x 5 x 3 ins., with cross  
marked (x), at base of post.

40.49 Intersect the W. Bdy. of Twp., at a point, S.0° 36' W.,  
3.31 chs. dist. from the cor. of secs. 24 and 25.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins.  
in the ground, for the closing cor. of secs. 19 and  
30, with brass cap mkd.

T46N	T46N	
R33E	S19	C
S25	S30	C
	R34E	
1923		

Deposit a granite stone, 6 x 5 x 2 ins., with cross  
marked (x) at base of post.

Land, rolling and broken. Soil, sandy and rocky with  
clay subsoil. Undergrowth, medium growth of sage and  
scattering bunch grass.

-----  
From the cor. of secs. 19, 20, 29 and 30.

N.0° 11' W., on a true line, bet. secs. 19 and 20

Desc. 50 ft. over rolling mountainous land.

9.10 Road, bears NE. and SW. Desc. 40 ft.

10.40 Dry wash, course SW. Asc. SE. slope 80 ft.

29.10 Short side draw, course SE. Asc. SE. slope 80 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.  
in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap  
mkd.