

## Survey of the subdivisions of T. 46 N., R. 34 E.

## Chains.

- 60.10 Top of spur, projects S. Desc. SW. slope 100 ft.  
 67.10 Dry wash, course S. Asc. SE. slope 50 ft.  
 74.90 Top of ridge, bears NE. and SW. Desc. NW. slope 80 ft.  
 79.84 The cor. of secs. 17, 18, 19 and 20.

Land, rolling mountainous. Soil, sandy and rocky clay loam. Undergrowth, medium growth of sage and bunch grass.

-----  
 West, on a true line, bet. secs. 18 and 19.

Desc. NW. slope 420 ft. over rolling mountainous land.

- 39.39 Intersect the W. Bdy. of Twp., at a point, S.0° 36' W.,  
 4.46 chs. dist. from the cor. of secs. 13 and 24.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins.  
 in the ground, for the closing cor. of secs. 18 and  
 19, with brass cap mkd.

	T46N	
T46N	S18	C
R33E	S19	C
S24	R34E	
	1923	

Deposit a granite stone, 12 x 7 x 6 ins., with cross  
 marked (x), at base of post.

Land, rolling mountainous. Soil, sandy and rocky with  
 clay subsoil. Undergrowth, medium growth of sage and  
 bunch grass.

-----  
 From the cor. of secs. 17, 18, 19 and 20.

N.0° 11' W., on a true line, bet. secs. 17 and 18.

Desc. NW. slope over rolling mountainous land.

- 17.80 Dry wash, 140 ft. below sec. cor., course W.  
 Asc. SW. slope 50 ft.

22.80 Top of spur, projects W. Desc. NW. slope 170 ft.

38.50 Dry wash, course W. Asc. SE. slope 10 ft.

- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.  
 in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap  
 mkd.

	$\frac{1}{4}$	
S18	S17	
	1923	