


Survey of the subdivisions of T. 46 N., R. 34 E.

Chains.

West, on a true line, bet. secs. 6 and 7.
Desc. along NW. slope 390 ft. over rolling mountainous land.

37.22 Intersect the W. Bdy. of Twp., at a point, S.0° 36' W.,
6.41 chs. dist. from the cor. of secs. 1 and 12.
Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 6 and 7, with brass cap mkd.



Raise a mound of stone, 2 ft. base, 1½ ft. high, E. of the cor.

Land, rolling mountainous. Soil, sandy and rocky with clay subsoil. Undergrowth, sage and bunch grass.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 08' W., on a random line, bet. secs. 5 and 6.

40.00 Set temp. ¼ sec. cor.

75.23 Fall 2 lks. W. of the cor. of secs. 5, 6, 31 and 32.

Thence

S.0° 07' E., on a true line, bet. secs. 5 and 6.

Asc. over rolling mountainous land.

8.20 Top of ridge, 120 ft. above sec. cor., bears NE. and SW.

Desc. SW. slope 350 ft.

35.23 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the ¼ sec. cor., with brass cap mkd.



Deposit a granite stone, 8 x 6 x 4 ins., with cross marked (x), at base of post.

41.30 Dry wash, 50 ft. below ¼ sec. cor., course W.

Asc. NW. slope 140 ft.

56.60 Top of spur, projects W. Desc. SW. slope 110 ft.

63.00 Dry wash, course W. Asc. NW. slope 40 ft.