

Dependent Resurvey of the E. Bdy. of T. 47 N., R. 34 E.

Chains.

Land, rough, broken and mountainous. Soil, rocky and gravelly clay. Undergrowth, scattering sage and scant growth of grass.

Survey of the W. Bdy. of T. 47 N., R. 34 E.

From the cor. of Ts. 46 and 47 N., R. 33 E., which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed as described in the field notes of T. 46 N., R. 34 E.,

North, on a true line, on the W. Bdy. of sec. 31. Asc. SW. slope over rough mountainous land.

10.60 Top of ridge, bears NE. and W. Desc. W. slope 200 ft.

28.09 A northing of 40.00 chs. from the closing cor. of Ts. 46 and 47 N., R. 34 E. Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 31, with brass cap mkd.

$\frac{1}{4}$
S31

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of the cor.

28.30 Top of spur, projects W. Desc. NW. slope 120 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 6 ins.

in the ground, to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor. for sec. 36, with brass cap mkd.

$\frac{1}{4}$
S36

1924 Deposit a granite stone, 12 x 12 x 5 ins., with cross marked (x), at base of post. Desc. NW. slope 240 ft.

49.50 Dry wash, course W. Asc. SW. slope 120 ft.

59.60 Top of spur, projects W. Desc. NW. slope 60 ft.

68.09 A northing of 80.00 chs. from the closing cor. of Ts. 46 and 47 N., R. 34 E. Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 30 and 31, with brass cap mkd.

T47N	T47N
R33E	S30
S36	S31
	R34E

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of the cor.

Land, rolling mountainous. Soil, light, sandy, loam over rocky granite subsoil. Undergrowth, medium growth of