

## Survey of the subdivisions of T. 47 N., R. 34 E.

Chains.	
39.00	Shallow wash, course N. $10^{\circ}$ E. Asc. gradual NE. slope.
44.00	Top of low spur, projects N. $10^{\circ}$ E. Desc. NW. slope 50 ft.
63.20	Dry wash, course N. $10^{\circ}$ E. Asc. E. slope 50 ft.
68.90	Top of low spur, projects N. $20^{\circ}$ E. Desc. gradual NW. slope.
70.70	Dim road, bears NE. and SW.
74.90	Wire fence, bears NE. and SW.
78.40	The cor. of secs. 1, 2, 11 and 12. Land, slightly rolling. Soil, sandy, gravelly and rocky clay loam. Undergrowth, medium growth of sage and scattering grass.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.40	Fall 35 lks. E. of the cor. of secs. 1, 2, 35 and 36, which is an iron post, 3 ins. in diam., 30 ins. above ground, firmly set in a mound of stone.
2.80	Road, bears SE. and NW. Asc. 50 ft.
10.40	Top of low ridge, bears E. and W. Desc. gradual S. 07.83
17.60	Road, bears E. and W. Desc. gradual S. slope.
26.30	Creek, running water, 1 lk. wide, 1 in. deep, course E.
36.40	Dry wash, course E. Asc. gradual N. slope.
40.40	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd. $S_2 \quad S_1$
45.40	Point of low spur, projects NE. Desc. gradual SE. slope.
61.80	Dry wash, course NE. Asc. gradual NW. slope.
68.70	Dim road, bears NE. and SW. Asc. NW. slope 80 ft.