

Survey of the subdivisions of T. 44 N., R. 35 E.

Chains.	
25.50	Top of spur, projects SE. Desc. broken and rocky SW. slope 120 ft.
33.38	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S5 \mid S4 \\ 1923 \end{array}$
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.
	Desc. SW. slope 200 ft.
50.40	Dry wash, course SE. Continue descent along SE. slope 60 ft.
66.80	Dry wash, course SE. Desc. 20 ft.
73.38	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling mountainous. Soil, rocky and sandy clay loam. Undergrowth, sage and scattering grass.
	From the cor. of secs. 5, 6, 31 and 32, on the S. Bdy. of the township, which is an iron post, 2 ins. in diam., 26 ins. above ground, firmly set in a mound of stone, with mound of stone W. of cor.,
	N. $0^{\circ} 04'$ W., on a true line, bet. secs. 31 and 32.
	Asc. SW. slope 410 ft. over rough mountainous land.
30.40	Top of spur, projects W. Desc. N. slope 50 ft.
35.00	Dry wash, course W. Asc. abrupt and rocky SW. slope 30 ft.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground, to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S31 \mid S32 \\ 1923 \end{array}$
	Deposit a red granite stone, 6 x 8 x 8 ins., with cross marked (x), at base of post.
	Asc. along broken and rocky SW. slope of ridge 900 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 20 ins.