

Survey of the subdivisions of T. 44 N., R. 35 E.

Chains.

- 18.20 Slope changes. Asc. 70 ft.
- 23.90 Point of rocky spur projects SE. Desc. SE. slope 210 ft. over red granite ledge.
- 33.38 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S6 | S5
 1923

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.

Desc. SE. slope 380 ft.

- 65.80 Dry wash, course SW.

- 73.38 The cor. of secs. 5, 6, 7 and 8.

Land, rolling and broken mountainous. Soil, rocky and sandy clay loam. Undergrowth, medium growth of sage and scattering grass.

Latitudes, Departures and Closing Errors.

Line Designated.	True Bearing.	Distance.	Latitudes.		Departures.	
			N.	S.	E.	W.
E. Bdy.	North	473.43	473.43			
N. Bdy.	West	463.40				463.40
W. Bdy.	South	473.32		473.32		
S. Bdy.	East	463.24			463.24	
Convergency						.64
			473.43	473.32	463.24	464.04
			473.32			463.24
Error in latitude				.11		
Error in departure						.80

General Description.

The portion of this township lying south of the ridge, which traverses the township in an easterly and westerly direction through secs. 25, 26, 27, 32, 33 and 34, is generally a high rolling mesa. The land to the north of the ridge slopes abruptly to low rolling and nearly level land. Sections 5, 6, 31 and 32