

Survey of the S. Bdy. of T. 43 N., R. 38 E.

Chains.

- 21.40 Top of spur, projects SW. Desc. SW. slope 580 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 30 ins.
 in the ground, on steep SW. slope, for the $\frac{1}{4}$ sec. cor.
 ✓ for sec. 32, with brass cap mkd.

$$\frac{1}{4} \text{ S32}$$

 1924

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of
 cor.

Desc. W. slope 220 ft.

- 46.70 Dry wash, course S. 30° W. Asc. SE. slope 150 ft.
 61.70 Top of ridge, bears NE. and SW. Desc. along S. slope
 420 ft.
 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins.
 in the ground, for the cor. of secs. 31 and 32, with
 ✓ brass cap mkd.

T43N	R38E
S31	S32
1924	

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of
 cor.

Land, rough mountainous. Soil, sandy, gravelly and rocky
 clay. Undergrowth, medium growth of sage and grass
 and scattering buckbrush. Aspen and willows along
 bottom of washes.

 West, on a true line, on the S. Bdy. of sec. 31.

Desc. SW. slope 70 ft. over rough mountainous land.

- 4.90 Head of dry wash, course SW. Asc. SE. slope 40 ft.
 13.50 Top of spur, projects SW. Desc. W. slope 100 ft.
 22.90 Slope changes to NE. asc. 30 ft.
 30.00 Top of short spur, projects N. Desc. NW. slope 250 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 30 ins.
 in the ground, on steep NW. slope, for the $\frac{1}{4}$ sec. cor.
 ✓ for sec. 31, with brass cap mkd.

$$\frac{1}{4} \text{ S31}$$

 1924

Deposit a granite stone, 8 x 8 x 4 ins., with cross
 marked (x), at base of post. No other accessories
 available.