

Survey of the subdivisions of T. 43 N., R. 38 E.

Chains.

- 72.30 Dry wash, course NE. Asc. along SE. slope 80 ft.
- 81.75 Intersect the N. Bdy. of the township, at a point,
S. $89^{\circ} 41' W.$, 6.59 chs. dist. from the cor. of secs.
34 and 35. At the point of intersection, set an iron
post, 3 ft. long, 2 ins. in diam., 27 ins. in the
ground, for the closing cor. of secs. 2 and 3, with
brass cap mkd.

T44N R38E

S34

S3 | S2

T43N R38E

C | C

1924

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of
the cor.

Land, rough mountainous. Soil, sandy, gravelly and rocky
clay over rocky quartzite formation. Undergrowth, sage,
buckbrush and good growth of grass. Timber, aspen.
Willows and chokecherry along bottom of creeks.

From the cor. of secs. 33 and 34 on the S. Bdy. of the
township, N. $0^{\circ} 02' W.$, on a true line, bet. secs.
33 and 34.

Asc. broken SE. slope 1100 ft. over rough mountainous
land to $\frac{1}{4}$ sec. cor.

- 14.30 Spring bears W., 50 lks. dist.
- 21.50 Spring heads on line.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 10 ins.
in the ground, to solid rock, and 26 ins. in a mound
of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S33 | S34

1924

Deposit a granite stone, 6 x 4 x 4 ins., with cross
marked (x), at base of post.

Asc. SE. slope 50 ft.

- 41.20 Top of ridge, bears E. and W. Desc. NE. slope 940 ft.
to creek.