


Subdivision of T. 30 N., R. 28 E.

Chains No suitable trees within limits  
 Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 14.05 Head of draw, drains N. 80° E.  
 Asc. SE. slope 20 ft. to  
 16.90 Spur, projects N. 80° E.  
 Desc. N. slope 125 ft. to  
 24.00 Main ravine, drains N. 75° E.  
 Asc. steep rocky SE. slope 75 ft. to  
 30.85 Draw, drains S. 20° E.  
 Asc. S. slope 235 ft. to  
 39.80 Spur, projects E.  
 Desc. NE. slope 50 ft. to ravine  
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 15 ins. in the  
 ground to solid rock, in a mound of stone, for the ¼  
 sec. cor., with brass cap mkd



No suitable trees within limits  
 At base of post deposit a mkd(X) granite stone, 3x3x4 ins.  
 42.90 Head of ravine, drains S. 75° E.  
 Asc. SW. slope 25 ft. to

47.47 Intersect Sixth Standard Parallel North, 54 lks. W. of  
 the standard cor. of secs. 35 and 36, and at point for  
 intersection  
 Set an iron post, 3 ft. long, 2 ins. dia., 12 ins. in the  
 ground to solid rock, in a mound of stone, for the  
 closing cor. of secs. 1 and 2, with brass cap mkd

