

## Subdivisions of T. 30 N., R. 28 E.

Chains Asc. SW. slope 115 ft. to  
 32.15 Spur, projects S. 80° W.  
 Desc. NW. slope 85 ft. to 40.10  
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 22 ins. in the  
 ground to solid rock, in a mound of stone, for the  $\frac{1}{4}$   
 sec. cor., with brass cap mkd  
 $\frac{1}{4}$   
 S3 | S2  
 1927  
 At base of post deposit a mkd(X) granite stone, 3x5x6 ins  
 40.10 Asc. SW. slope 15 ft. to  
 42.80 Desc. NW. slope 10 ft. to  
 46.20 Bottom of Granite Springs Canyon, drains S. 25° W.  
 Asc. SE. slope 35 ft. to  
 47.69 Intersect the Sixth Standard Parallel North, .78 chs.  
 W. of the standard cor. of secs. 34 and 35, and at  
 point of intersection  
 Set an iron post, 3 ft. long, 2 ins. dia., 4 ins. in the  
 ground to solid rock, in a mound of stone, for the  
 closing cor. of secs. 2 and 3, with brass cap mkd  
 T3 1NR28E  
 S. 34  
 S3 | S2  
 T3 1NR28E  
 CC  
 1927  
 At base of post deposit a mkd(X) granite stone, 4x5x7 ins.  
 Land, rough mountainous. Soil, rocky.  
 Timber, few isolated juniper. Undergrowth, sage.  
 General drainage, SE. and SW. Grazing, fair.  
 From the cor. of secs. 3, 4, 33 and 34  
 N. 0° 02' W., between secs. 33 and 34  
 Over rough mountainous land  
 Asc. SW. slope 25 ft. to  
 2.15 Spur, projects N. 70° W.  
 Desc. NW. slope 60 ft. to