

Subdivisions of T. 30 N., R. 28 E.

Chains

44.80 Ravine, drains S. 65° W. 8 chs.

Asc. SE. slope 40 ft. to

47.57  
211

Intersect Sixth Standard Parallel North, 56 chs. W. of the standard cor. of secs. 33 and 34, and at point of intersection

Set an iron post, 3 ft. long, 2 ins. dia., 12 ins. in the ground, to solid rock, for the closing cor. of secs. 3 and 4, with brass cap mkd

T31N R28E

S33

S4 | S3

T30N R28E

CC

1927

At base of post deposit a mkd(X) granite stone, 1x4x6 ins.

No suitable trees available within limits

Land, rough mountainous. Soil, rocky.

Timber, scattering juniper. Undergrowth, sage.

General drainage, SW. Grazing, poor.

From the cor. of secs. 4, 5, 32, and 33, on S. boundary of township

N. 0° 03' W., between secs. 32 and 33

Over mountainous land

Asc. SE. slope 130 ft. to 24.90

12.60 Draw, drains S. 40° E. about 4 chs. to main draw

24.90 Desc. NE. slope

28.00 Draw, drains S. 45° E.

Asc. SE. slope 200 ft. to ridge

36.35 Draw, drains S. 30° E.

40.00 On SE. slope

Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the ground, to solid rock, in a mound of stone, for the 1/4 sec. cor., with brass cap mkd

S32 | S33

1927