


Subdivisions of T. 30 N., R. 28 E.


Chains Asc. SE. slope 125 ft. to 24.05
 22.15 Ridge, bears N. 20° E. and S. 50° W.
 24.05 Desc. NW. slope 20 ft. to
 25.35 Head of ravine, drains N. 65° W.
 Asc. steep rocky SW. slope 190 ft. to
 38.45 Ridge in bend, bears N. 20° E. and S. 50° E.
 Desc. steep NW. slope 85 ft. to 45.20
 40.00 On W. slope of rock outcropping
 Set an iron post, 3 ft. long, 1 in. dia., over a chiseled
 (X) cross, in a mound of stone, for the 1/4 sec. cor.,
 with brass cap mkd



No suitable trees available within limits

45.20 Asc. rocky SW. slope 50 ft. to
 47.00 Rocky spur, projects N. 60° W.
 Desc. rocky NW. slope 15 ft. to
 47.61 Intersect the Sixth Standard Parallel North, .60 chs. W.
 of the standard cor. of secs. 32 and 33, and at point
 of intersection

Set an iron post, 3 ft. long, 2 ins. dia., 8 ins. in the
 ground to solid rock, in a mound of stone, for the
 closing cor. of secs. 4 and 5, with brass cap mkd



At base of post deposit a mkd(X) granite stone, 4x4x6 ins.
 No suitable trees available within limits

Land, rough mountainous. Soil, rocky.
 Timber, scattering juniper. Undergrowth, sage.
 General drainage, NW. and SE. Grazing, poor.