

## Survey of W. boundary T. 32 N., R. 28 E.

Chains

40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd

$\frac{1}{4}$   
S12 | S7  
1927

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

56.55 Wash in draw, 15 lks. wide, 2 ft. deep, drains N.  $45^\circ$  E.

Asc. SE. slope 25 ft. to

74.95 Point of spur, projects SE. Desc. NE. slope 15 ft. to

80.00 On NE. slope

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the cor. of secs. 1, 6, 7 and 12, with brass cap mkd

T32N  
R27E R28E  
S1 | S6  
S12 | S7  
1927

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling. Soil, gravelly and rocky.

Timber, none. Undergrowth, sagebrush, shadscale.

General drainage, NE. Grazing, poor.

North, between secs. 1 and 6

Over rolling land. Asc. general SE. slope 75 ft. to 46.80

18.00 Draw, drains S.  $30^\circ$  E.

32.45 Wash in draw, 30 lks. wide, 4 ft. deep, drains S.  $65^\circ$  E.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the ground to solid rock, in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd

$\frac{1}{4}$   
S1 | S6  
1927

At base of post deposit a marked (X) stone, 2x3x5 ins.

40.50 Low flat ridge, bears N.  $65^\circ$  W. and S.  $65^\circ$  E.