

Dependent Resurvey of Portion of
Sixth Standard Parallel North

Chains

T31NR29E
S36
S1 | S6
R29E | R30E
T30N
CC
1927

✓
39.20 Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.
Old road, bears N. 60° W. and S. 60° E.
40.00 Standard ¼ sec. cor.
West, on dependent resurvey, continuing measurement.
41.66 At mid-point between closing cor. to T. 30 N., Rs. 29 and
30 E., and closing cor. to secs. 1 and 2, T. 30 N., R.
29 E.

✓
Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
ground, for the ¼ sec. cor. of sec. 1 only, with brass
cap mkd

¼ S1
1927

43.00 Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.
Surface wash, drains S. 30° E.
53.80 Wash, 8 lks. wide, 2 ft. deep, drains S. 45° E.
80.00 Standard cor. of secs. 35 and 36

Land, practically level. Soil, sandy loam.
Timber, none. Undergrowth, sagebrush.
General drainage, SE. Grazing, poor.

Dependent Resurvey of Portion of Subdivisions
T. 31 N., R. 29 E.

From the old cor. of secs. 1, 2, 11, and 12, which is a
basalt stone, firmly set in the ground, marked and
witnessed as described in the original field notes,
alongside which

✓
Set an iron post, 3 ft. long, 2 ins. dia., 18 ins. in
rocky ground, in a mound of stone, for the cor. of secs.
1 and 12 only, with brass cap mkd

T31NR29E
S1
S2 ———
S12
1927

At base of post deposit a marked (X) stone, 2x4x6 ins.