

Dependent Resurvey of Portion of Subdivisions T. 31 N., R. 29 E.

Chains Set an iron post, 3 ft. long, 1 in. dia., 4 ins. in the ground to solid rock, in a mound of stone, for the $\frac{1}{4}$

sec. cor., with brass cap mkd

$\frac{1}{4}$ S 12
S 13
1927

At base of post deposit a marked (X) stone, 2x6x6 ins.

The bearing of this half mile is N. 89° 50' W., and the distance 40.07 chs.

From the cor. of secs. 1, 6, 7, and 12, on the E. boundary of township

West, on retracement between secs. 1 and 12

40.20 Fall 3 lks. N. of the old $\frac{1}{4}$ sec. cor., which is a lava stone, firmly set in the ground, marked and witnessed as described in the original field notes, alongside which

Set an iron post, 3 ft. long, 1 in. dia., 1 $\frac{1}{2}$ ins. in the ground to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd

$\frac{1}{4}$ S 1.
S 12
1927

At base of post deposit a marked (X) stone, 3x6x8 ins.

The bearing of this half mile is S. 89° 57' W., and the distance 40.20 chs.

West, on retracement from $\frac{1}{4}$ sec. cor., continuing measurement

80.43 Intersect the cor. of secs. 1 and 12

The bearing of this half mile is West, and the distance 40.23 chs.

Survey of Portion of Sixth Standard Parallel North
Through Range 29 East

From the standard cor. of secs. 35 and 36, T. 31 N., R. 29 E.

West, on S. boundary of sec. 35

Over practically level land