

Dependent Resurvey of portion of S. bdy. of T. 27 N., R. 52 E.

Chains

41.90 Rocky spur, projects S. Desc. SE. slope
 50.40 Draw, drains SW. Asc. W. slope
 58.30 Ridge, bears SE. and NW. Desc. E. slope
 65.90 Head of draw, drains NW. Asc. E. slope
 66.00 Ridge, bears NE. and SW. Desc. E. slope
 80.04 The cor. of Ts. 26 and 27 N., R. 52 E.
 Land, rolling mountainous. Soil, rocky.
 Timber, juniper, and pinon. Undergrowth, sage.
 General drainage, NW. Grazing, good.

Dependent Resurvey of portion of N. bdy. of T. 27 N., R. 52 E.

I begin at the old cor. of secs. 3, 4, 33, and 34, which
 is a charred post, with evidences of mound of earth
 and pits, alongside post

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in
 the ground, for the cor. of secs. 3, 4, 33, and 34,
 with brass cap mkd

T28N

S33 S34

S4 S3

T27NR52E

1926

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Thence

East on retracement bet. secs. 3 and 34

40.09 Fall $1\frac{1}{4}$ lks. S. of the old $\frac{1}{4}$ sec. cor., which is a
 charred post, with evidences of pits and mound of
 earth, alongside post

Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
 ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd

 $\frac{1}{4}$ S 34

S 3

1926

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

The bearing of this half mile is therefore, N. $89^{\circ} 48'$ E.,
 and the dist. 40.09 chs.