

Dependent Resurvey and Survey of portion of Subdivisions
T. 27 N., R. 52 E.

Chains	
80.04	Fall 14 lks. W. of the old 1869 cor. of secs. 2, 3, 34, and 35, which is a charred post, marked and witnessed, as described in the original field notes, I destroy all traces of same
83.82	Intersect N. bdy. of Twp., S. $84^{\circ} 33'$ W., 47 lks. from the cor. of secs. 34 and 35, and at point of intersection Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the closing cor. for secs. 2 and 3, with brass cap mkd T28N S34 S3 S2 T27NR52E CC 1926 Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor. Land, gently rolling. Soil, gravelly clay. Timber, none. Undergrowth, sage. General drainage, W. Grazing, fair.
	From the cor. of secs. 2, 3, 10, and 11 S. $89^{\circ} 27'$ W., on Dependent Resurvey bet. secs. 3, and 10 Over rolling land
2.10	Draw, drains N. Asc. gentle NE. slope
7.30	Spur, projects N. Desc. NW. slope
12.30	Draw, drains N. Thence along general N. slope across numerous spurs and draws.
40.05	The $\frac{1}{4}$ sec. cor. Thence S. $88^{\circ} 37'$ W., on Dependent Resurvey, continuing measurement
49.20	Wash, 10 lks. wide, 1 ft. deep, drains N.
58.70	Wash, 10 lks. wide, 2 ft. deep, drains N.
66.40	Road, bears NW. and SE.
70.00	Spur, projects NW. Desc. gentle SW. slope 25 ft. to
80.22	The cor. of secs. 3, 4, 9, and 10.