

Chains Subdivisions T. 27 N., R. 53 E.

9.90 Old road, bears NW. and SE.

13.60 Head of draw, drains SW. Asc. SE. slope 20 ft. to

21.40 Spur ridge, bears NE. and SW. Desc. NW. slope 100 ft. to

40.00 On NW. slope

Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd

$\frac{1}{4}$ S 31
 S 6
 1926

No stone available.

Dig pits on line, one east and one west of cor.

Desc. 100 ft. to

57.00 Desc. precipitous W. slope 180 ft. to

62.00 Wash in ravine, 10 lks. wide, 3 ft. deep, drains NW.

Asc. abrupt NE. slope 50 ft. to

68.80 Small draw, drains NE. Asc. abrupt E. slope 140 ft. to

75.25 Asc. gentle E. slope 60 ft. to twp. cor.

77.00 Enter timber, bears NW. and SE.

84.95 The cor. of T. 28 N., Rs. 52 and 53 E.

Thence

N. 89° 54' W., bet. secs. 6 and 36, continuing measurement

88.19 The closing cor. of T. 27 N., Rs. 52 and 53 E., which is described in Book "D", containing the field notes of survey of frac. T. 27 N., R. 52 E., under Group No. 111

Land, rolling mountainous. Soil, clay loam.

Timber, pinon, juniper, and mountain mahogany.

Undergrowth, sage. General drainage, NW. Grazing, fair.

Subdivisions T. 27 N., R. 53 E.

From the cor. of secs. 1, 2, 35, and 26, on S. bdy. of twp.

N. 0° 01' W., bet. secs. 35 and 36

Over gently rolling land

24.00 General ascent of SE. slope 265 ft. to ridge

40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd

$\frac{1}{4}$
 S35 | S36
 1924