

Survey of a portion of the N. boundary T. 28 N., R. 53 E.

- Chains.
- 41.60 Head of draw, drains NW. Asc. NE. slope
  - 44.25 Spur, projects N. Desc. NW. slope to
  - 46.35 Draw, drains N. Asc. NE. slope 80 ft. to
  - 54.50 Rocky spur, projects NW. Enter scattering timber, bears NW. and SE. Desc. SW. slope 270 ft. to
  - 66.50 Ravine, drains NW. Asc. NE. slope
  - 69.85 Spur, projects NW. Desc. SW. slope 170 ft. to ravine.
  - 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the cor. of secs. 3 and 4 only, with brass cap mkd

T29NR53E

S4 | S3

T28N

1926

Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor. Thence along same line continuing measurement on N. boundary of sec, 4

- 81.05 Ravine, drains NW. Slight Ascent of NE. slope to
- 85.17 Cor. of secs. 33 and 34, T. 29 N., R. 53 E. Land, mountainous. Soil, gravelly clay. Timber, mountain mahogany. Undergrowth, sagebrush, service berry. General drainage, SE. and NW. Grazing, fair.

Dependent Resurvey of Portion of N. boundary  
T. 28 N., R. 53 E.

From the cor. of secs. 33 and 34, T. 29 N., R. 53 E. West, on retracement on S. boundary of sec. 33

- 39.64 Intersect ¼ sec. cor. bet. secs. 33 and 4, which is a 1 in. iron post, firmly set in the ground, properly marked and witnessed as described in the original field notes of survey of fractional T. 29 N., R. 53 E., I remark corner to read as follows

¼ S 33

1927

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. The bearing of this half mile, is therefore West, and the