

Subdivisions T. 28 N., R. 53 E.

Chains	From the cor. of secs. 1, 2, 35 and 36, on S. bdy. of twp., which is described in the field notes of the survey of T. 27 N., R. 53 E. made in conjunction with the survey of this township
	N. 0° 01' W., bet. secs. 35 and 36
	Over rough mountainous land. Asc. steep SW. slope 330 ft. to
11.15	Rocky spur, projects W. Desc. N. slope 50 ft. to
19.15	Ravine, drains W., heads about 15 chs. E. Asc. SW. slope 60 ft. to
28.00	Spur, projects W. Desc. NW. slope 25 ft. to
31.80	Ravine, drains SW., heads about 15 chs. E. Asc. SW. slope 130 ft. to spur
40.00	On SW. slope
	Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in rocky ground, in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd
	$\frac{1}{4}$
	S35 S36
	1926
	At base of post deposit a marked (X) stone, 1x2x3 ins
42.50	Spur, projects SW. Desc. NW. slope 30 ft. to
48.75	Ravine, drains W. Desc. 110 ft. along W. slope
65.25	Ravine, drains SW., heads about 20 chs. E. Asc. SW. slope 350 ft. to
79.65	High rocky spur, projects W. Thence along W. slope
80.00	On W. slope
	Set an iron post, 3 ft. long, 2 ins. dia., 14 ins. in rocky ground, in a mound of stone, for the cor. of, secs. 25, 26, 35 and 36, with brass cap mkd
	T28NR53E
	S26 S25
	S35 S36
	1926