

Survey of E. boundary T. 28 N., R. 54 E.

Chains Land, rolling bench. Soil gravelly clay.
 Timber, none. Undergrowth, sagebrush.
 General drainage, E. Grazing, poor.
 Note: Diligent search was made at regular intervals of 40.00 and 80.00 chs. for the old $\frac{1}{4}$ sec. and sec. cors., but no evidence was found of any of them.

Chains Survey of S. boundary T. 28 N., R. 54 E.

From the cor. of Ts. 28 N., Rs. 54 and 55 E.
 West on a random line, setting temp. $\frac{1}{4}$ sec. and sec. cors at regular intervals of 40.00 and 80.00 chs., and at
 425.37 Fall 12 lks. S. of the cor. of Ts. 27 and 28 N., Rs. 53 and 54 E., which is described in the survey of T. 27 N., R. 53 E., the survey of which was made in conjunction with the survey of this township. (Group No. 111)
 The bearing of the S. boundary of this township, is therefor, N. 89° 59' W., and the distance 425.37 chs.

From the cor. of Ts. 28 N., Rs. 54 and 55 E.
 N. 89° 59' W., on true S. bdy. of twp. and sec. 36
 Over rolling land

4.20 Surface wash, drains SE.
 21.50 Wash, 20 lks. wide, 3 ft. deep, drains SE.
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in rocky ground, in a mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap mkd

$\frac{1}{4}$ S 36

1926

At base of post, deposit a mkd(X) stone, 6X5X3 ins.
 43.40 Same wash, drains NE. Asc. SE. slope 10 ft. to spur
 46.00 Enter scattering timber and point of spur, projects S. Thence along gentle SW. slope
 48.10 Small ravine, drains SE. Asc. NE. slope 65 ft. to
 67.85 Low Spur, projects SE. Thence along SW. slope
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the cor. of secs. 35 and 36 only, with brass cap mkd