

DEPENDENT RESURVEY OF W. BOUNDARY T. 26 N., R. 40 E.

Chains

50.35 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 6 only, with brass cap mkd

$\frac{1}{4}$

S6

1928

No stone available for mound; pits impracticable
At base of post deposit a mkd(X) limestone, 6x4x2 ins.

58.50 Old road, bears N. 45° E. and S. 45° W.

80.00 Northing of 480.00 chs. from the SE. standard cor. of T. 26 N., R. 39 E., and easting of 160.00 chs. from the cor. of secs. 2, 3, 34, and 35, T. 26 N., R. 39 E.

Set an iron post, 3 ft. long, 3 ins. dia., 27 ins. in the ground, for the cor. of Ts. 26 and 27 N., R. 39 E., with brass cap mkd

T27NR39E

S36

T26N

S6

S1

R40E

T26N

1928

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
Thence

North, on original survey on W. boundary of sec. 6,
continuing measurement

Over level land

103.08 Point for the cor. of Ts. 26 and 27 N., R. 40 E.,
hereinafter described

Land, rolling to level. Soil, sandy clay.

Timber, none. Undergrowth, sage, shadscale, rabbit brush.

General drainage, SW. Grazing, poor.

DEPENDENT RESURVEY OF A PORTION OF 5TH. STD. PAR. N.
T. 26 N., R. 40 E

RANDOM LINES

(Reestablishment of Surveys executed by D. H. Barker and W. W. Skinner, under Contract No. 72, year 1875)