

DEPENDENT RESURVEY OF A PORTION OF 5TH. STD. PAR. N.
T. 26 N., R. 40 E.

Chains I begin at the standard cor. of Ts. 26 N., Rs. 40 and 41 E., hereinafter described

Thence
West, on retracement on S. boundary of sec. 36

40.00 Find no trace of the standard $\frac{1}{4}$ sec. cor.

80.26 Fall 6 lks. S. of the standard cor. of secs. 35 and 36, hereinafter described

The bearing of this mile is therefore, N. $89^{\circ} 57' W.$, and the distance 80.26 chs.

West, on retracement from standard sec. cor., on S. boundary of sec. 35

40.45 Fall 2 lks. S. of the old standard $\frac{1}{4}$ sec. cor., hereinafter described

The bearing of this half mile is therefore, N. $89^{\circ} 58' W.$, and the distance 40.45 chs.

Thence
West, on retracement from standard $\frac{1}{4}$ sec. cor., continuing measurement

81.03 Fall 7 lks. S. of the standard cor. of secs. 34 and 35, hereinafter described

The bearing of this half mile is therefore N. $89^{\circ} 54' W.$, and the distance 40.58 chs.

West, on retracement from standard sec. cor. on S. boundary of sec. 34

40.00 Find no trace of standard $\frac{1}{4}$ sec. cor.

80.00 Find no trace of standard cor. of secs. 33 and 34

TRUE LINES

I return to standard cor. of Ts. 26 N., Rs. 40 and 41 E., which is a porphyry stone, firmly set in the ground, marked SC and 6 notches N., E., S., and W. faces, alongside which