

SURVEY OF A PORTION OF 5TH. STD. PAR. N. T 26 N., R. 40 E.

Chains	West, on S. boundary of sec. 32
	Over rough mountainous land through scattering timber
	Desc. NW. slope 130 ft. to
6.55	Ravine, drains NW.
	Asc. NE. slope 55 ft. to
8.85	Desc. NW. slope 40 ft. to
16.95	Main ravine, drains N. 35° E.
	Asc. steep rocky SE. slope 385 ft. to 47.00
40.00	Set an iron post, 3 ft. long, 1 in. dia., 22 ins. in the ground to solid rock, in a mound of stone, for the standard $\frac{1}{4}$ sec. cor., with brass cap mkd
	$\frac{1}{4} \begin{array}{c} SC \\ S 32 \end{array}$ 1928
	At base of post deposit a mkd(X) limestone, 6x4x4 ins.
47.00	Ravine, drains SE.
	Asc. NE. slope 585 ft. to
70.45	Spur, projects N. 20° E.
	Desc. along N. slope 65 ft. to
78.30	Head of ravine, drains N. 45° E.
	Asc. NE. slope 25 ft. to
80.00	Set an iron post, 3 ft. long, 2 ins. dia., 8 ins. in the ground to solid rock, in a mound of stone, for the standard cor. of secs. 31 and 32, with brass cap mkd
	$\begin{array}{c} SC \\ T26NR40E \\ \hline S31 \quad S32 \\ \hline 1928 \end{array}$
	At base of post deposit a mkd(X) basalt stone, 6x4x4 ins.
	Land, rough mountainous. Soil, rocky.
	Timber, juniper. Undergrowth, sage.
	General drainage, NE. Grazing, fair.
	West, on S. boundary of sec. 31
	Over rough mountainous land