

SURVEY OF E. BOUNDARY T. 26 N., R. 40 E.

Chains From the standard cor. of Ts. 26 N., Rs. 40 and 41 E. North, between secs. 31 and 36  
 Over rolling mountainous land  
 Desc. NW. slope  
 5.00 Draw, drains SW.  
 Asc. SW. slope 75 ft. to  
 16.15 Low spur, projects SW.  
 Desc. NW. slope 10 ft. to  
 26.75 Draw, drains SW.  
 Asc. S. slope 125 ft. to  
 35.00 Asc. SE. slope 175 ft. to 62.30  
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the ground to solid rock, in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd  

$$\begin{array}{c} \frac{1}{4} \\ S36 \mid S31 \\ \cdot 1928 \end{array}$$
 At base of post deposit a mkd(X) granite stone, 6x4x4 ins.  
 62.30 Spur, projects W.  
 Desc. NW. slope 25 ft. to  
 65.50 Head of draw, drains W.  
 Asc. SW. slope 125 ft. to  
 79.00 Spur, projects W.  
 Desc. NW. slope  
 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the cor. of secs. 25, 30, 31, and 36, with brass cap mkd  

$$\begin{array}{c} T26N \\ R40E \mid R41E \\ S25 \mid S30 \\ S36 \mid S31 \\ \cdot 1928 \end{array}$$
 Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.