

## Dependent Resurvey of a portion of the N. Bdy. of

T. 28 N., R. 41 E.

Chains.

for the cor. of secs. 1 and 2, only, with brass cap mkd.

T29N R41E.

S35

S2 | S1

T28N R41E

1926

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of the cor.

- 79.82 The old cor. of secs. 1, 2, 35 and 36, hereinbefore described. Alongside, set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 35 and 36, only, with brass cap mkd.

T29N R41E

S35 | S36

S1

T28N R41E

1926

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of the cor.

Land, slightly rolling. Soil, light gravelly and rocky sand. Undergrowth, shadscale; scant growth of grass.

No timber.

N.  $89^{\circ} 42'$  E., on a true line, on the S. Bdy. of sec. 36.

Asc. gradual NW. slope over slightly rolling land.

- 23.00 Shallow wash, drains NW. Asc. abrupt rocky W. slope of spur, 120 ft.

- 27.90 Top of spur, projects NW. Desc. rocky E. slope 30 ft.

- 30.80 Dry wash, drains NW. Asc. SW. slope 30 ft.

- 36.55 A westing of 40.00 chs. from the closing cor. of T. 28 N., Rs. 41 and 42 E., hereinafter determined. Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground for the  $\frac{1}{4}$  sec. cor. of sec. 1, only, with brass cap mkd.

S1

1926

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of the cor.

Asc. SW. slope 90 ft.

- 40.00 The proportionate point. Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of sec. 36, only, with brass cap mkd.