

Dependent resurvey of a portion of the subdivisions of

T. 28 N., R. 41 E.

Chains. At base of post, deposit a granite stone, 8 x 8 x 5 ins., marked with cross (x).

Desc. along gradual N. slope.

74.12 Intersect the cor. of secs. 2, 3, 34 and 35, hereinbefore described.

Land, slightly rolling. Soil, light, sandy, gravelly and rocky clay. Undergrowth, medium growth of shadscale; sage along bottom of washes; sparse growth of grass.

No timber.

Survey of a portion of the subdivisions of T. 28 N., R. 41 E.

From the cor. of secs. 1, 2, 35 and 36, on the S. Bdy. of the township, which is an iron post, 3 ins. in diam., firmly set, properly marked and witnessed, as described in the field notes of T. 27 N., R. 41 E., N. 0° 01' W., bet. secs. 35 and 36.

Asc. SW. slope 170 ft. over rolling mountainous land.

17.20 Top of spur, projects SW. Desc. NW. slope 120 ft.

28.30 Dry wash, drains SW. Asc. SE. slope 210 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground, to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S35 | S36
 1926

At base of post, deposit a granite stone, 10 x 10 x 8 ins., marked with cross (x). Pits impracticable and no other accessories available.

Asc. SE. slope 20 ft.

41.20 Top of spur, projects SW. Desc. NW. slope 55 ft.

52.20 Slope changes to SW. Asc. 70 ft.

61.10 Top of spur, projects W. Desc. N. slope 130 ft.

75.70 Dry wash, drains W. Asc. S. slope 60 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 14 ins. in the ground, to solid rock, in a mound of stone, for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd.