

Survey of a portion of the subdivisions of T. 28 N., R. 41 E.

Chains. closing cor. of secs. 2 and 11, with brass cap mkd.

	T28N	
S10	S2	C
	S11	C
	R41E	
	1926	

At base of post, deposit a granite stone, 10 x 6 x 6 ins. marked with cross (x) Pits impracticable and no other accessories available.

From the cor. of secs. 1, 2, 11 and 12,
North, on a random line, bet. secs. 1 and 2.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

75.95 Fall 17 lks. E. of the cor. of secs. 1 and 2, on the N.
Bdy. of the township.

Thence

S. $0^{\circ} 07'$ E., on a true line, bet. secs. 1 and 2.

Asc. general NW. slope 60 ft. overslightly rolling land.

22.90 Dry wash, drains NW.

35.95 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.
in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

	$\frac{1}{4}$	
S2		S1
	1926	

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of
the cor.

Asc. 40 ft. over general NW. slope.

55.50 Dry wash, drains NW.

66.50 Dry wash, drains NW.

75.95 Intersect the cor. of secs. 1, 2, 11 and 12.

Land, slightly rolling. Soil, light, sandy, gravelly
and rocky clay. Undergrowth, shadscale; sparse growth
of grass. No. timber.

From the cor. of secs. 2, 3, 34 and 35, on the S. Bdy.
of the township, which is an iron post, 3 ins. in diam.,
firmly set, properly marked and witnessed, as described
in the field notes of T. 27 N., R. 41 E.

N. $0^{\circ} 02'$ W., bet. secs. 34 and 35.