

## Survey of a portion of the subdivisions of T.28 N., R.41 E.

Chains.  
79.64

Intersect the S. Bdy. of sec. 8, at a point, S.89°49'W.,  
227 lks. distant from the cor. of secs. 8 and 9, here-  
inbefore described.

At the point of intersection, set an iron post, 3 ft.  
long, 2 ins. in diam., over a cross (x) on solid rock,  
in a mound of stone, 7 ft. base, 36 ins. high, for the  
closing cor. of secs. 16 and 17, with brass cap mkd.

S8  
S17 | S16  
T28N | R41E  
C | C  
1926

Land, rolling. Soil, sandy, gravelly and rocky clay.

Undergrowth, shadscale; sparse growth of grass.

No timber.

From the cor. of secs. 5, 6 31 and 32, on the S. Bdy. of  
the township, which is an iron post, 3 ins. in diam.,  
firmly set, properly marked and witnessed, as described  
in the field notes of T. 27 N., R. 41 E.,  
N. 0° 04' W., bet. secs. 31 and 32.

Asc. SE. slope 80 ft. over broken mountainous land,  
through scattering juniper.

9.50 Top of ridge, bears E. and W. Desc. broken NW. slope  
370 ft.

34.60 Dry wash, drains NW. Asc. S. slope 40 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.  
in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S31 | S32  
1926

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of  
the cor.

Asc. S. slope 30 ft.

45.00 Top of spur, projects NW. from E. Desc. N. slope 340 ft.

60.30 Dry wash, drains W. Asc. S. slope 60 ft.

66.50 Top of spur, projects W. Desc. N. slope 90 ft.

72.00 Dry wash, course W. Asc. S. slope 30 ft.