

## Survey of a portion of the subdivisions of T.28 N., R.41 E.

Chains.

West, on a true line, bet. secs. 19 and 30.

Asc. NE. slope 10 ft. over rolling land.

3.50 Top of low spur, projects NW. Desc. broken NW. slope  
320 ft.

33.90 Dry wash, drains NW. Asc. NE. slope 20 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.  
in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{r} \frac{1}{4} \\ \hline S19 \\ S30 \\ 1926 \end{array}$$
Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of  
the cor.

Asc. NE. slope 40 ft.

43.60 Top of spur, projects NW. Desc. SW. slope 80 ft.

56.20 Dry wash, drains NW.

59.70 Dry wash, drains NW.

65.00 Dry wash, drains NW.

77.40 Dry wash, drains NW.

78.12 Intersect the W. Bdy. of the township, at a point,  
North, 4.38 chs. distant, from the cor. of secs. 24  
and 25, which is an iron post, 2 ins. in diam., firmly  
set and properly marked and witnessed as described in  
the field notes of T. 28 N., R. 40 E.At the point of intersection, set an iron post, 3 ft.  
long, 2 ins. in diam., 27 ins. in the ground, for the  
closing cor. of secs. 19 and 30, with brass cap mkd.
$$\begin{array}{r|l} & T28N \\ T28N & S19 \quad C \\ R40E & S30 \quad C \\ S24 & R41E \\ & 1926 \end{array}$$
Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of  
the cor.Land, rolling. Soil, light, sandy, gravelly and rocky  
clay. Undergrowth, shadscale; scant growth of grass.

No timber.