

Survey of the S. Bdy. of T. 23 N., R. 46 E.

Chains. From the old cor. of Ts. 22 and 23 N., Rs. 46 and 47 E., which is a pine post, 3 ft. long, 4 ins. square, marked with 6 notches on each face,

West, on a random line, setting temp. points at 40.00 and 80.00 chs.

493.54 Fall 8.38 chs. S. of the cor. of Ts. 22 and 23 N., Rs. 45 and 46 E., which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed.

Thence

East, on a true line, on the S. Bdy. of sec. 31.

Desc. SE. slope 90 ft. over rough mountainous land.

11.40 Head of dry wash, course S. Asc. SW. slope 150 ft.

22.80 Top of junction of two spur, projecting NE. and SE.

Desc. abrupt E. slope 810 ft.

50.40 Dry wash, course N. 10° E. Asc. gradual NW. slope.

53.54 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 31, with brass cap mkd.

$\frac{1}{4}$ S31 ✓

1925

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the cor.

54.30 Spring bears N., 5.00 chs. dist.

Asc. abrupt NW. slope 170 ft.

61.30 Top of spur, projects N. 30° W. Desc. NE. slope 90 ft.

65.90 Dry wash, course N. Asc. W. slope 120 ft.

74.70 Top of spur, projects N.

81.50 Top of spur, projects NE. Desc. E. slope 50 ft.

85.70 Head of dry wash, course N. Asc. W. slope 30 ft.

92.50 Top of spur, projects NW. Desc. E. slope 10 ft.

93.54 Set an iron post, 3 ft. long, 2 ins. in diam., 14 ins. in the ground, to solid rock, and 20 ins. in a mound of stone, for the cor. of secs. 31 and 32, with brass cap mkd.

T23N | R46E ✓
S31 | S32
 T22N R46E
 1925